



Art. 415

Chiusino Circolare ø 500 mm apertura ribaltamento e bandiera
Round lid ø 500 mm riverse and side opening
Trappe circolare ø 500 mm ouverture par renversement et laterale
Boca circular ø 500 mm levantamiento vertical y lateral
Domdeckel ø 500 mm mit Schwenk-und Seitenöffnung

a saldare - welding - à souder
para soldar - Schweissausführung

Ø 500 mm

Pressione massima
Max pressure
Pression maxima
Presión máxima
Max Betriebsdruck

0.2 bar

Coperchio con Accessori
Cover with Accessories
Couvercle avec Accessoires
Tapa con Accesorios
Deckmel mit Zubehör



Art.	AISI	S mm	Peso kg Weight
CA41515A	304	1.5	6
CA41515B	316	1.5	6

Art.	AISI	H mm	T mm	S mm	P max bar	Peso kg Weight
4150652015A	304	65	2	1.5	0,2	8,7
4151002015A	304	100	2	1.5	0,2	9,6
4151502015A	304	150	2	1.5	0,2	10,9
4152002015A	304	200	2	1.5	0,2	12,2
4154002015A	304	400	2	1.5	0,2	17,3
4154702015A	304	470	2	1.5	0,2	18,8
4150652015B	316	65	2	1.5	0,2	8,7
4151002015B	316	100	2	1.5	0,2	9,6
4151502015B	316	150	2	1.5	0,2	10,9
4152002015B	316	200	2	1.5	0,2	12,2
4154002015B	316	400	2	1.5	0,2	17,3
4154702015B	316	470	2	1.5	0,2	18,8

H = Altezza telaio mm
Frame Heigt mm
Hauteur cadre mm
Altura marco mm
Hohe des Rahmens mm

T = Spessore telaio mm
Frame thickness mm
Epaisseur cadre mm
Espesor marco mm
Starke des Rhamens mm

S = Spessore coperchio mm
Cover thickness mm
Epaisseur portillon mm
Espesor porton mm
Starke des Deckels mm

